



Bombardier Recreational Products
10101 Science Drive
Sturtevant, WI 53177
www.evinrude.com



Sundance Boats, Inc.
6131 Sundance Road
Blackshear, GA 31516
912-449-0033
www.sundanceboats.com



2008 Sundance SV186

BOAT

2008 Sundance SV186

Material: Fiberglass
Length: 18' 6"
Beam: 90"
Weight w/o Engine: 1570 LBS Dry
Maximum HP: 115 HP
Fuel Capacity: 40 Gallons
Transom height: 25" Shaft
Steering: Uflex NFB

ENGINE

2008 Evinrude® 115 HP ETEC®

Engine Type: Loop-Charged 60° V 4
Horsepower: 115HP @ 5750 RPM
Displacement: 105.4 CC
Induction: ETEC DFI
Operating Range: 5500-6000 RPM
Weight: 375 LBS Dry Weight
Gear Ratio: 2.25:1

PROPELLER

BRP Viper™ TBX

Material: Stainless Steel
Diameter/Pitch: 14.75" x 17"
No. of Blades: 3
Part Number: 763914

MOUNTING HEIGHT

Hole Position: #2
Jack Plate: N/A
AV Mounting: N/A

PERFORMANCE DATA

RPM	MPH	GPH	MPG	RANGE
500	2.3	0.18	12.9	464
1000	3.8	0.24	16.3	586
1500	5.7	0.52	11.0	395
2000	6.8	1.14	6.0	215
2500	7.7	2.65	2.9	104
3000	10.1	3.84	2.6	95
3500	21.6	4.12	5.2	189
4000	26.5	4.76	5.6	200
4500	30.3	6.11	5.0	178
5000	34.4	7.12	4.8	174
5500	37.8	9.24	4.1	147
5650	38.9	10.06	4.3	154

Range (Miles) Based on 90% Fuel Capacity

TEST CONDITIONS

Water Conditions: Calm
Wind Velocity: 1-3 MPH
Air Temperature: 68° F
Fuel Load: 36 Gallons
Weight: 2 Men(400 lbs) Fuel, Test Gear ,1 Batt.

PERFORMANCE SUMMARY

Top Speed: **38.9 MPH**
Best Fuel Efficiency: **5.6 MPG with a range of 200 miles @ 26.5 MPH**
Acceleration: **4.38 seconds to plane**



NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.

© 2008 BRP US Inc. All rights reserved.

™ ® Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.

